

# DAKSeco V3.10

Last modified: 5 February 2026

Performance feature / hardware detail	DAKSeco 110 based on DAKS-110 hardware	DAKSeco 200 based on DAKS-200 hardware
Housing/dimensions	desktop unit (165mm x 105mm x 45mm)	19" server (1U) for rack mounting
Number of parallel telephony channels	5 to 10	5 to 30
TC network connection technology	VoIP trunking (encrypted/unencrypted)	
Signaling protocols	QSIG, CorNet-NQ, SIP, SIP-Q, NI2	
Voice codecs	G.711, A-law or $\mu$ -law	
Computer and operating system	64-bit ARM Cortex-A53 w/ Linux™ operating system	<ul style="list-style-type: none"> <li>computer core 1 w/ <math>\mu</math>CLinux™ operating system</li> <li>computer core 2 w/ Linux™ operating system</li> </ul>
Mass storage <i>for program, data, licenses, logs and announcements</i>	pluggable Industrial Grade microSD card	pluggable Industrial Grade CompactFlash card
LAN interfaces <i>for VoIP, VCON service access, administration via browser and peripheral connection via ESPA-X, Syslog, NTP, SNMP and printer protocol (Raw/Port 9001)</i>	1x 10/100/1000BASE-T (GbE)	2x 10/100BASE-T (separate IP addresses) <ul style="list-style-type: none"> <li>optionally one or two LAN connections</li> <li>VoIP separately if needed</li> </ul>
Serial ports <i>galvanically isolated</i>	2x RS232/RS422/RS485 w/ ESPA 4.4.4/TAP protocol	
USB interface <i>for commissioning and service</i>	1x (Type C)	1x (Type B)
Log printer connection	optionally via LAN or via USB	
Power supply	via Power-over-Ethernet (PoE Class 3)	<ul style="list-style-type: none"> <li>via two separate internal power supplies, optionally from 24/48VDC or 115/230VAC (for redundancy purposes also in parallel)</li> <li>in connection with an external AC/DC converter also supply from 2x 115/230VAC</li> </ul>
Power consumption	approx. 12 watts	<ul style="list-style-type: none"> <li>with AC: approx. 25 watts</li> <li>with DC: approx. 20 watts</li> </ul>
Digital I/O	on the device: <ul style="list-style-type: none"> <li>16 digital inputs (monitored)</li> <li>8 digital outputs</li> <li>1 special relay output (normally open/ normally closed), e.g. for last-error message</li> </ul> via USB gateway (IOG-03A): <ul style="list-style-type: none"> <li>up to 32/64 digital inputs (monitored/ non-monitored), also mixed</li> <li>up to 16 digital outputs</li> </ul>	on the device: <ul style="list-style-type: none"> <li>1 special relay output (normally open/ normally closed), e.g. for last-error message</li> </ul> via USB gateway (IOG-03A): <ul style="list-style-type: none"> <li>up to 32/64 digital inputs (monitored/ non-monitored), also mixed</li> <li>up to 16 digital outputs</li> </ul> via DAKS-Satellite (max. 5x), each with: <ul style="list-style-type: none"> <li>16 digital inputs (monitored)</li> <li>8 digital outputs</li> <li>1 special relay output (normally open/ normally closed), e.g. for last-error message</li> </ul>

Performance feature / hardware detail	DAKSeco 110 based on DAKS-110 hardware	DAKSeco 200 based on DAKS-200 hardware
Time synchronization	via NTP	via NTP, or optionally via DCF77 port on the device (additional hardware required)
Country approvals <i>Country codes acc. to ISO 3166</i>	CE, FCC for: <ul style="list-style-type: none"> <li>All EU countries: AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK</li> <li>Non-EU countries: AU, CA, CH, CO, GB, HK, ID, ME, MK, MY, NZ, PA, PH, RS, SG*, TR, US</li> </ul> * Singapore: available as industrial product only	CE, FCC, and Australia RCM for: <ul style="list-style-type: none"> <li>All EU countries: AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK</li> <li>Non-EU countries: AR*, AU, CA, CO, CH, GB, HK, ID, ME, MK, MY, NZ, PA, PH, RS, SG**, TR, US</li> </ul> * Argentina: 48V version only ** Singapore: available as industrial product only  <i>As of Oct. 12, 2020 (subject to change)</i>

## The strengths of DAKSeco V3.10 at a glance

- Connection via VoIP to practically all PBXs, carrier networks or soft switches (unencrypted or encrypted)
- Connection of host data interfaces serially (2x RS232/RS422/RS485) and via ESPA-X (max. 5x)
- Flexible broadcasting processes in multitasking with priority control (up to 1,000 broadcast groups)
- Emergency conferences with participant dial-up and Phone Meeting Points with dial-in option
- Broadcast activation via SNMP traps, via Node-RED, via contact inputs, from nurse call or BMS/SCADA systems, control panels, web dashboards, via telephone or e-mail
- Simple location of terminal devices in DECT and WLAN networks (output of the Visited Station or Visited Access Point)
- Support via LAN of remote DAKS-Satellites for additional contact I/O and serial interfaces
- Alerting/notification via phone calls, e-mail, DAKS Mobile Client (DMC), OAP messaging, Gigaset AML, Mitel messaging, Spectralink XML RPC/MSF-3 messaging, or contact outputs with downstream acoustic or optical signalers
- Up to 1,000 announcements from wave files or via ad-hoc telephone recording
- Comfortable administration via browser GUI
- Extensive logging (audit-proof)
- Security mechanisms for adaptation to special security requirements
- Particularly high availability and durability → very high sustainability due to long operating time and hardware support



Silberbachstr. 10  
65232 Taunusstein-Wehen  
Germany

Phone: +49 6128 963-0  
Fax: +49 6128 963-499  
Email: info@tetronik.com  
Website: www.tetronik.com

DAKSeco V3.10 – Data Sheet | ID: 101777863 v25 | Copyright © 2026 tetronik GmbH. All rights reserved.

Disclaimer: The information in this document contains only general descriptions or performance features that do not always apply as described in a specific application. This is the case, for example, if certain options have not been ordered or if products change in the course of further development. Performance features are only binding if they were expressly agreed upon conclusion of the contract.

Last modified: 5 February 2026